

# 2.5 x 2.0 x 0.95 mm 32.768kHz CERAMIC SURFACE MOUNT CRYSTAL OSCILLATOR



2.5 x 2.0 x 0.95 mm

ASDK Series



ESD Sensitive



RoHS/RoHS II Compliant

## FEATURES:

- 32.768kHz in 2.5 x 2.0 x 0.95mm package
- Seam sealed assure high reliability performance
- Low current consumption 1.0mA (Vdd=1.8V)
- Suitable for RoHS compliant reflow
- Extend temperature range available

## APPLICATIONS:


- Laptop
- Digital camera
- Wireless LAN
- Bluetooth and mobile communication
- LCD
- PDA and MP3 player
- Electricity, gas and water metering

## STANDARD SPECIFICATIONS:

Parameters	Minimum	Typical	Maximum	Units	Notes
Frequency Range	-----	32.768	-----	kHz	
Operating Temperature	0	-----	+70	°C	See options
Storage Temperature	-55	-----	+125	°C	
Overall Frequency Stability	-100	-----	+100	ppm	See options
Supply Voltage (Vdd)	2.97	3.3	3.66	V	Standard
	2.375	2.5	2.625		Option 1
	1.71	1.8	1.89		Option 2
Supply Current (I <sub>dd</sub> )	-----	1.0	1.5	mA	Vdd=1.8V
	-----	1.2	2.5		Vdd=2.5V
	-----	2.2	3.5		Vdd=3.3V
Output Load	-----	-----	15	pF	CMOS
Output Voltage	V <sub>OH</sub>	0.9*Vdd	-----	V	
	V <sub>OL</sub>	-----	0.1*Vdd		
Tri-state function	"1" (V <sub>IH</sub> ≥2.0V or open) : Oscillation "0" (V <sub>IL</sub> <0.8V) : Hi Z				
Aging	-3.0	-----	+3.0	ppm	@+25°C First year
Symmetry @1/2Vdd	40	50	60	%	Standard
	45	50	55		Option S
Start-up Time	-----	28	35	ms	
Rise/Fall Time (Tr/Tf)	-----	43	50	ns	
Disable Current	-----		10	μA	

## OPTIONS AND PART IDENTIFICATION (Left blank if standard)

ASDK  - 32 768kHz -  -  -  -



Supply Voltage
Blank: 3.3V±10%
1: 2.5 V±5%
2: 1.8 V±5%

Operating Temp.
Blank: 0°C ~ +70°C
E: -20°C ~ +70°C
F: -30°C ~ +70°C
N: -30°C ~ +85°C
L: -40°C ~ +85°C

Overall Freq. Stability
Blank: ±100ppm
J: ±20ppm (**)
R: ±25ppm
K: ±30 ppm
C: ±50 ppm

Symmetry
Blank: 40/60%
S: 45/55%

Packaging
Blank: Bulk
T: Tape & Reel

\*Contact ABRACON for extended temperature range

\*\* For Temp option E, F, N and 0° C to +70° C only



# 2.5 x 2.0 x 0.95 mm 32.768kHz CERAMIC SURFACE MOUNT CRYSTAL OSCILLATOR



2.5 x 2.0 x 0.95 mm

ASDK Series




ESD Sensitive





RoHS/RoHS II Compliant

## OUTLINE DRAWING:



## TAPE & REEL:(1,000pcs/reel)

## REFLOW PROFILE



Need a test socket for the ASDK Series? To view compatible **PRECISION TEST & BURN-IN SOCKETS** for these parts, [click here](#). **AXS-2520-04-07**

**ATTENTION:** Abracon Corporation's products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependant Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon Corporation is required. Please contact Abracon Corporation for more information.

ABRACON IS  
ISO 9001:2008  
CERTIFIED



Visit [www.abracon.com](http://www.abracon.com) for Terms & Conditions of Sale  
30332 Esperanza, Rancho Santa Margarita, California 92688  
tel 949-546-8000 | fax 949-546-8001 | [www.abracon.com](http://www.abracon.com)

Revised: 05.13.16